

Maintenance and service are essential

Failure to perform the necessary cleaning and maintenance will result in long-term devaluation of the solar shading system.

Soiling of the slats and the lift tapes and ladder braids significantly impairs the blind's function and may lead to corrosion damage.



Before

After

Regular cleaning not only ensures that the systems function properly, but also gives them the aesthetic appearance of architecturally valuable facades.

HD VARIO 3

Cleaning of external venetian blinds on the facade

- ▲ For cleaning of 50, 60, 70, 80, 90, and 100 mm slats
- ▲ Easy to use
- ▲ Cleaning without chemicals
- ▲ Lift tapes and ladder braids are also cleaned
- ▲ Perfect cleaning result
- ▲ Time savings of 40-60%.

2.1 kg



HD VARIO 3

Cleaning of external venetian blinds on the facade



sps-cleaning-systems GmbH & Co.KG

Miquelallee 191, 60320 Frankfurt am Main, Germany

Phone: +49 (0)69 28 60 63 84, Fax: +49 (0)69 28 60 63 85

e-mail: info@sps-cleaning.net

www.sps-cleaning.net

Copyright sps-cleaning-systems 2018

- Subject to technical change without prior notice -



Specifications

For the cleaning of

50, 60, 70, 80, 90 and 100 mm slats



Drive

High-pressure cleaner
(Not included)

Weight of handset/brushes	2.1 kg
Power supply	230 V / 50 Hz
Power consumption	about 3,3 kWh
Water connection	2 – 5 bar
Water consumption	11 l/min.

Area output (depending on blind accessibility) **1m² in 4 minutes**

HD VARIO 3

Cleaning is carried out **directly on site on the facade** in an environmentally friendly manner that does not involve chemicals.



The cleaning system offers the perfect entry-level solution for cleaning external blinds on the facade. Driven by high pressure, the **rotating brush rollers** clean the tops and bottoms of the slats simultaneously. Lift tapes and ladder braids are also cleaned and guarantee the value-preserving cleaning and functionality of the venetian blinds.



The optional use of **fully demineralized water** ensures residue-free cleaning and drying of the slats.

With six brush sizes that can be selected as required and are perfectly matched to the different slat widths, **all slat sizes from 50-100 mm** can be cleaned.



Brush replacement is very straightforward, and spacing between brushes can be precisely adjusted to the required slat width. The **ergonomic** one-handed operation offers a safe and comfortable working environment.

